

CI/SfB	(47)	Tn
CAW P10		
Uniclass L6812		
December 2009		

CP Protection Series

A Range of Protection Courses for Waterproof Membranes

Tremco illbruck offers a complete range of protection courses for use over Tremco CP250 waterproofing membrane and similar buried waterproof membranes. Designed to suit a variety of traffic and installation conditions, these materials can be installed directly over the cured membrane to provide immediate and long-term protection from vehicular and pedestrian traffic, backfill and other trades. Use either as stand-alone protection or in conjunction with Tremco CP650 drainage mat. Refer to individual product data sheets for further details on storage, handling and installation.

TREMCO CP620

Description

Tremco CP620 is a modified bitumen protection course heavy-duty protection of buried waterproof membranes.

Usage / Purpose

Tremco CP620 is used as a heavy duty protection course for protection over Tremco CP250 or other waterproofing membranes. Primarily used in horizontal applications subject to heavy vehicular or pedestrian traffic. Avoid exposure to solvents, oils or other contaminants harmful to asphaltic materials.

Composition

SBS modified bitumen sheet.

Colour

Black

Packaging

1 m wide x 20 m roll

Mass

2.4 kg/m²

TREMCO CP630

Description

Tremco CP630 is a lightweight polypropylene sheet for protection of buried waterproof membranes.

Usage / Purpose

Tremco CP630 is used as lightweight protection over Tremco CP250 or other waterproof membranes. It is ideal for use in horizontal applications subject only to pedestrian traffic during installation of the membrane. Also ideally suited to backfilled walls and similar vertical installations.

LIMITATIONS

Not suitable for vehicular or heavy / prolonged pedestrian traffic.

Composition

Thermally bonded, non-woven UV-stabilised polypropylene geotextile.

Colour

White

Packaging

1.2 m wide x 100 m roll

Mass

0.25 kg/m²

TREMCO CP640

Description

Tremco CP640 is a high density polyethylene sheet used to provide an impermeable root-proof barrier.

Usage / Purpose

Tremco CP640 is used in conjunction with the Tremco CP250 waterproofing system. Once installed over the cured membrane, Tremco CP640 protects the membrane from root penetration in green roof systems, planters and similar installations.

Composition

High density polyethylene (HDPE) sheet.

Colour

Black

Packaging

1.2 m x 50 m rolls

Mass

0.8 kg/m²

Technical Service

Tremco illbruck has a team of experienced Technical Sales Representatives who provide assistance in the selection and specification of products. For more detailed information, service and advice, please call Customer Services on 01942 251400.

Guarantee / Warranty

Tremco illbruck products are manufactured to rigid standards of quality. Any product which has been applied (a) in accordance with Tremco illbruck written instructions and (b) in any application recommended by Tremco illbruck, but which is proved to be defective, will be replaced free of charge. No liability can be accepted for the information provided in this leaflet although it is published in good faith and believed to be correct. Tremco illbruck Limited reserves the right to alter product specifications without prior notice, in line with Company policy of continuous development and improvement.



CP Protection Series

Tremco illbruck Limited
Coupland Road
Hindley Green, Wigan WN2 4HT UK
Tel: 01942 251400
Fax: 01942 251410
Email: uk.info@tremco-illbruck.com
Website: www.tremco-illbruck.co.uk