

CI/SfB	(43)	Vv1
CAW Z20		
Uniclass L68245:P7102		
August 2010		

# CS150

## Acrylic Primer

### KEY BENEFITS SUMMARY

- Removes the adverse effects of suction from the substrate including pin-holing and premature drying of the screed, which result in the loss of desired flow characteristics

### PRODUCT INFORMATION

#### Description

Tremco CS150 Acrylic Primer is a universal primer for porous substrates.

#### Usage / Purpose

Tremco CS150 Acrylic Primer is specifically designed for use as a primer for polymer screed applications or beneath smoothing compounds on porous substrates.

#### Colour

White

#### Packaging

25 litres and 5 litres.

#### Availability

Direct from Tremco illbruck (see back of leaflet for address and telephone details), or via local and national distributors.

### TECHNICAL INFORMATION

#### Composition

Aqueous based co-polymer dispersion.

#### Characteristics (Typical Values)

DENSITY

1.02 g/ml

pH

7-9

#### Performance (Typical Values)

SOLUBILITY IN WATER

Miscible

FREEZING POINT

0°C

### USAGE GUIDELINES

#### Standards

All aspects of the installation must be in accordance with the requirements of BS8204, BS8203 (Installation of Resilient Floorcoverings) or BS5325 (Installation of Textile Floorcoverings) and supplementary specifications.

#### Surface Preparation

- Ensure all surfaces to be coated are clean, dry, frost free and free from grease, oil, dirt, dust, loose friable material and any other contaminants.
- Mechanical preparation, using an enclosed shotblasting machine, may be recommended and should be followed by thorough vacuuming to remove all surface dust.

#### Method of Application

Apply by brush or roller ensuring a continuous film, avoiding puddles and ensuring all the surface is coated.

#### Coverage Rate

8 m<sup>2</sup> per litre depending on substrate.

#### Health & Safety Precautions

Product Health and Safety Data Sheet must be read and understood before use.

#### Storage

Store in dry, shaded conditions between +5°C and +35°C.

#### Shelf Life

6 months when stored as recommended in original unopened packaging.

#### Technical Service

Tremco illbruck has a team of experienced Technical Sales Representatives who provide assistance in the selection and specification of products. For more detailed information, service and advice, please call Customer Services on 01942 251400.

#### Guarantee / Warranty

Tremco illbruck products are manufactured to rigid standards of quality. Any product which has been applied (a) in accordance with Tremco illbruck written instructions and (b) in any application recommended by Tremco illbruck, but which is proved to be defective, will be replaced free of charge.

No liability can be accepted for the information provided in this leaflet although it is published in good faith and believed to be correct.

Tremco illbruck Limited reserves the right to alter product specifications without prior notice, in line with Company policy of continuous development and improvement.

# CS150

Tremco illbruck Limited  
Coupland Road  
Hindley Green, Wigan WN2 4HT UK  
Tel: 01942 251400  
Fax: 01942 251410  
Email: uk.info@tremco-illbruck.com  
Website: www.tremco-illbruck.co.uk

