



## SAFETY DATA SHEET

### CS300 PU SCREED (formerly MONOFLOOR ST) - CURATIVE

#### 1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME	CS300 PU SCREED (formerly MONOFLOOR ST) - CURATIVE
PRODUCT NO.	10870
APPLICATION	Floor screed component
SUPPLIER	Tremco illbruck Production Ltd Coupland Rd Hindley Green Wigan WN2 4HT England Phone: +44 (0) 1942 251400 Fax: +44 (0) 1942 521923 msds@tremco-illbruck.com
EMERGENCY TELEPHONE	+44 (0) 1942 258011

#### 2 HAZARDS IDENTIFICATION

Harmful by inhalation.

May cause sensitisation by inhalation.

Irritating to eyes, respiratory system and skin.

CLASSIFICATION Xn;R20. R42. Xi;R36/37/38.

#### 3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification
DIPHENYLMETHANEDIISOCYANATE -Isomers & homologues		9016-87-9	60-100%	Xn;R20. Xi;R36/37/38. R42.

The Full Text for all R-Phrases are Displayed in Section 16

#### 4 FIRST-AID MEASURES

##### INHALATION

Move the exposed person to fresh air at once. Get medical attention. Provide rest, warmth and fresh air. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen.

##### INGESTION

DO NOT INDUCE VOMITING! NEVER MAKE AN UNCONSCIOUS PERSON VOMIT OR DRINK FLUIDS! Rinse mouth thoroughly. Drink plenty of water. Get medical attention immediately!

##### SKIN CONTACT

Remove contaminated clothing. Wash the skin immediately with soap and water. Get medical attention promptly if symptoms occur after washing.

##### EYE CONTACT

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes and get medical attention.

#### 5 FIRE-FIGHTING MEASURES

##### EXTINGUISHING MEDIA

Small fires:

Powder.

# CS300 PU SCREED (formerly MONOFLOOR ST) - CURATIVE

Foam.

DO NOT use water if avoidable.

Larger fires:

Water spray.

**SPECIAL FIRE FIGHTING PROCEDURES**

Do not get water inside container. NOTE! Use air-supplied respirators to protect against gases/fumes.

## 6 ACCIDENTAL RELEASE MEASURES

**PERSONAL PRECAUTIONS**

Wear protective clothing as described in Section 8 of this safety data sheet.

**SPILL CLEAN UP METHODS**

Wear necessary protective equipment. Ventilate well. Avoid contact with skin or inhalation of spillage, dust or vapour. Avoid water on spilled material or leaking containers. Collect with absorbent, non-combustible material into suitable containers. If material is contaminated with water containers must be vented. Containers with collected spillage must be properly labelled with correct contents and hazard symbol. Do not contaminate water sources or sewer.

## 7 HANDLING AND STORAGE

**USAGE PRECAUTIONS**

Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level.

**STORAGE PRECAUTIONS**

Keep in original container. Store in tightly closed original container in a dry, cool and well-ventilated place.

## 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Name	Std	TWA - 8 hrs		STEL - 15 min		Notes
DIPHENYLMETHANEDIISOCYANATE -Isomers & homologues	WEL		0.02 mg/m3(Sen)		0.07 mg/m3(Sen)	

WEL = Workplace Exposure Limit.

**PROTECTIVE EQUIPMENT**



**ENGINEERING MEASURES**

Must not be handled in confined space without sufficient ventilation.

**RESPIRATORY EQUIPMENT**

If ventilation is insufficient, suitable respiratory protection must be provided.

**HAND PROTECTION**

Use protective gloves made of: Butyl rubber. Rubber (natural, latex). Neoprene.

**EYE PROTECTION**

Wear approved safety goggles. Use face shield in case of splash risk.

**OTHER PROTECTION**

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

## 9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Liquid		
COLOUR	Dark Brown		
SOLUBILITY	Immiscible with water Reacts with water		
BOILING POINT (°C)	>200°C 760 mm Hg	RELATIVE DENSITY	1.2 @ 25° c
FLASH POINT (°C)	>200°C Not noted.		

# CS300 PU SCREED (formerly MONOFLOOR ST) - CURATIVE

## 10 STABILITY AND REACTIVITY

### STABILITY

Stable under normal temperature conditions and recommended use.

### CONDITIONS TO AVOID

Reacts with water forming carbon dioxide which may cause pressure to rise in a sealed container.

### MATERIALS TO AVOID

Acid reactive. Water reactive material.

### HAZARDOUS DECOMPOSITION PRODUCTS

Fire creates: Toxic gases/vapours/fumes of: Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>). Cyanides. Oxides of: Nitrogen.

## 11 TOXICOLOGICAL INFORMATION

### INHALATION

May cause irritation to the respiratory system. May cause sensitisation by inhalation.

### INGESTION

May cause discomfort if swallowed.

### SKIN CONTACT

May cause skin irritation/eczema. May cause sensitisation by skin contact.

### EYE CONTACT

May cause severe irritation to eyes.

### TARGET ORGANS

Skin. Eyes. Respiratory system, lungs.

## 12 ECOLOGICAL INFORMATION

### ECOTOXICITY

Little danger to the environment.

### BIOACCUMULATION

Reacts with water. Reaction product has no potential for bioaccumulation.

### DEGRADABILITY

Not biodegradable

### ACUTE FISH TOXICITY

Low toxicity to aquatic organisms

## 13 DISPOSAL CONSIDERATIONS

### GENERAL INFORMATION

Waste product is classified as Hazardous Waste

Waste to be treated as controlled waste. Disposal to licensed waste disposal site in accordance with local Waste Disposal Authority.

### DISPOSAL METHODS

Contact specialist disposal companies.

In the UK refer to the Hazardous Waste Regulations (2005)

### WASTE CLASS

Hazard Classification: H4, H5 EWC Code: 08 04 09

## 14 TRANSPORT INFORMATION

### GENERAL

Not classified as hazardous for transport

### MARINE POLLUTANT

No.

## 15 REGULATORY INFORMATION

# CS300 PU SCREED (formerly MONOFLOOR ST) - CURATIVE

## LABELLING



Harmful

## CONTAINS

DIPHENYLMETHANEDIISOCYANATE -Isomers & homologues

## RISK PHRASES

R20 Harmful by inhalation.  
R42 May cause sensitisation by inhalation.  
R36/37/38 Irritating to eyes, respiratory system and skin.

## SAFETY PHRASES

S23 Do not breathe vapour/spray.  
S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.  
S37 Wear suitable gloves.  
S38 In case of insufficient ventilation, wear suitable respiratory equipment.  
S45 In case of accident or if you feel unwell, seek medical advice immediately (show label where possible).  
S24/25 Avoid contact with skin and eyes.  
P4 Contains isocyanates. See information supplied by the manufacturer.

## UK REGULATORY REFERENCES

Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 ("CHIP 4")

## EU DIRECTIVES

Dangerous Preparations Directive 1999/45/EC

## GUIDANCE NOTES

Workplace Exposure Limits EH40.

## 16 OTHER INFORMATION

### REVISION COMMENTS

NOTE: Lines within the margin indicate significant changes from the previous revision.

REVISION DATE 14/12/2009

REV. NO./REPL. SDS GENERATED 10/06/2008

SDS NO. 10892

### RISK PHRASES IN FULL

R20 Harmful by inhalation.  
R36/37/38 Irritating to eyes, respiratory system and skin.  
R42 May cause sensitisation by inhalation.