



SAFETY DATA SHEET

ES200 FASTRAK UNIVERSAL PART A (formerly TREADFAST)

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME	ES200 FASTRAK UNIVERSAL PART A (formerly TREADFAST)
PRODUCT NO.	10607
APPLICATION	One part of a two part floor coating membrane
SUPPLIER	Tremco illbruck Coatings Ltd Coupland Rd Hindley Green Wigan WN2 4HT England Phone: +44 (0) 1942 251400 Phone: +44 (0) 1942 258011 Fax: +44 (0) 1942 521923 msds@tremco-illbruck.com
EMERGENCY TELEPHONE	+44 (0) 1942 251400 (UK)

2 HAZARDS IDENTIFICATION

Irritating to eyes and skin.

May cause sensitisation by skin contact.

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

CLASSIFICATION (1999/45) Xi;R36/38. R43. N;R51/53.

3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification (67/548)
1-METHYL-2-PYRROLIDONE	212-828-1	872-50-4	< 0.5%	Repr. Cat. 2;R61. Xi;R36/37/38.
BISPHENOL F EPOXY RESIN		9003-36-5	5-10%	Xi;R36/38. N;R51/53. R43.
EPOXY RESIN (Number average MW <= 700)	500-033-5	25068-38-6	30-60%	R43 Xi;R36/38 N;R51/53
OXIRANE, MONO [(C12-14-ALKYLOXY) METHYL] DERIVS	271-846-8	68609-97-2	5-10%	Xi;R38. R43.

The Full Text for all R-Phrases are Displayed in Section 16

4 FIRST-AID MEASURES

INHALATION

Move the exposed person to fresh air at once. Keep the affected person warm and at rest. Get prompt medical attention.

INGESTION

DO NOT INDUCE VOMITING! Immediately rinse mouth and provide fresh air. Get medical attention immediately!

SKIN CONTACT

Remove affected person from source of contamination. Remove contaminated clothing. Wash the skin immediately with soap and water. Get medical attention if any discomfort continues.

EYE CONTACT

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes and get medical attention.

5 FIRE-FIGHTING MEASURES

ES200 FASTRAK UNIVERSAL PART A (formerly TREADFAST)

EXTINGUISHING MEDIA

Fire can be extinguished using:

Water spray, fog or mist.

Foam.

Powder.

DO NOT USE: Water jet.

6 ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS

Wear protective clothing as described in Section 8 of this safety data sheet.

ENVIRONMENTAL PRECAUTIONS

Do not discharge into drains, water courses or onto the ground.

SPILL CLEAN UP METHODS

Absorb in vermiculite, dry sand or earth and place into containers.

7 HANDLING AND STORAGE

USAGE PRECAUTIONS

Avoid spilling, skin and eye contact. Persons susceptible to allergic reactions should not handle this product.

STORAGE PRECAUTIONS

Store in tightly closed original container in a dry, cool and well-ventilated place.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Name	Std	TWA - 8 hrs		STEL - 15 min		Notes
1-METHYL-2-PYRROLIDONE	WEL	25 ppm	103 mg/m3	75 ppm	309 mg/m3	Sk

WEL = Workplace Exposure Limit.

Sk = Can be absorbed through skin.

PROTECTIVE EQUIPMENT



ENGINEERING MEASURES

Provide adequate general and local exhaust ventilation.

HAND PROTECTION

Use protective gloves made of: Rubber or plastic.

EYE PROTECTION

Wear approved safety goggles.

OTHER PROTECTION

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Paste		
COLOUR	Beige.		
ODOUR	Characteristic		
SOLUBILITY	Insoluble in water		
BOILING POINT (°C)	>200°C 760 mm Hg	RELATIVE DENSITY	1.73 @ 25°C
VISCOSITY	2400 cps @ 25°C	FLASH POINT (°C)	>200°C Not noted.
VOLATILE ORGANIC COMPOUND (VOC)	0 g/litre		

10 STABILITY AND REACTIVITY

ES200 FASTRAK UNIVERSAL PART A (formerly TREADFAST)

STABILITY

Stable under normal temperature conditions and recommended use.

MATERIALS TO AVOID

Strong acids. Strong alkalis. Peroxides.

HAZARDOUS DECOMPOSITION PRODUCTS

High temperatures generate: Toxic gases/vapours/fumes of: Carbon dioxide (CO₂). Carbon monoxide (CO).

11 TOXICOLOGICAL INFORMATION

SKIN CONTACT

Irritating to skin. May cause sensitisation by skin contact.

EYE CONTACT

Irritating to eyes.

12 ECOLOGICAL INFORMATION

ECOTOXICITY

Dangerous for the environment: Degrades very slowly in nature.

BIOACCUMULATION

Medium potential for bioaccumulation

DEGRADABILITY

The product is expected to be slowly biodegradable.

ACUTE FISH TOXICITY

Very toxic to aquatic organisms.

13 DISPOSAL CONSIDERATIONS

GENERAL INFORMATION

Waste is classified as hazardous waste. Disposal to licensed waste disposal site in accordance with the local Waste Disposal Authority.

Fully cured product is not hazardous

DISPOSAL METHODS

In the UK refer to the Hazardous Waste Regulations (2005)

WASTE CLASS

EWC Code: 08 04 09 Hazard Classification: H4 H14

14 TRANSPORT INFORMATION



PROPER SHIPPING NAME	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, NOS		
PROPER SHIPPING NAME	EPOXY RESIN MIXTURE		
UN NO. ROAD	3082	ADR CLASS NO.	9
ADR CLASS	Class 9: Miscellaneous dangerous substances and articles.	ADR PACK GROUP	III
TUNNEL RESTRICTION CODE	(E)	RID CLASS NO.	9
UN NO. SEA	3082	IMDG CLASS	9
UN NO. AIR	3082	AIR CLASS	9

15 REGULATORY INFORMATION

LABELLING

ES200 FASTRAK UNIVERSAL PART A (formerly TREADFAST)



Irritant



Dangerous for the environment

CONTAINS

BISPHENOL F EPOXY RESIN
EPOXY RESIN (Number average MW <= 700)
OXIRANE, MONO [(C12-14-ALKYLOXY) METHYL] DERIVS

RISK PHRASES

R43	May cause sensitisation by skin contact.
R36/38	Irritating to eyes and skin.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

SAFETY PHRASES

S24/25	Avoid contact with skin and eyes.
S26	In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
S37	Wear suitable gloves.
S61	Avoid release to the environment. Refer to special instructions/safety data sheets.
P5	Contains epoxy constituents. See information supplied by the manufacturer.

UK REGULATORY REFERENCES

Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 ("CHIP 4")

EU DIRECTIVES

Dangerous Preparations Directive 1999/45/EC

GUIDANCE NOTES

Workplace Exposure Limits EH40.

16 OTHER INFORMATION

REVISION COMMENTS

NOTE: Lines within the margin indicate significant changes from the previous revision.

REVISION DATE	15/02/2011
REV. NO./REPL. SDS GENERATED	13/08/2010
SDS NO.	10486

RISK PHRASES IN FULL

R36/38	Irritating to eyes and skin.
R36/37/38	Irritating to eyes, respiratory system and skin.
R38	Irritating to skin.
R61	May cause harm to the unborn child.
R43	May cause sensitisation by skin contact.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.