

Jacksons Glass

Surrey

Penetrating Epoxy Primer

- Tremco Penetrating Epoxy Primer is based on a blend of epoxy resin and curing agent binder giving the low viscosity characteristics necessary to wet the substrate, giving good penetration properties.
- This product can be used as a tack coat or as a general purpose primer beneath the Tremco range of industrial screeds.

Epoxicote

- Tremco Epoxicote is a high build, thickly applied solvent free coating possessing excellent wear and acid resistance. The finished product is attractive and tough enough to withstand industrial usage. Once cured, Epoxicote offers excellent chemical and abrasion resistance.
- Tremco Epoxicote Aggregate is also available, for use where a slip resistant surface is required.

This 1,200 square metre old floor was worn, damaged, dirty and oil contaminated after many years regular use. The remedial specification involved shotblasting and hot compressed air burning to remove the contamination, followed by two coats of Penetrating Epoxy Primer, the second coat blinded with Rapide Aggregate No7.

After the primer had cured overnight, 6 mm thickness of Treadfast Uniflow was applied by pump. Half of the floor area was covered in only two hours.

After overnight cure the floor was hard and suitable for pedestrian and vehicle traffic.

Although not always necessary, the customer chose to have the screed painted with the highly durable Epoxicote system. The resulting floor is smooth, very hard wearing and easily cleaned.

Due to storage capacity constraints, the customer required the area to be treated in two halves. The difference between before and after is remarkable as seen in the photo. The project was completed exactly to requirements.



TREMCO