



SAFETY DATA SHEET TREADFAST UNITEX PART A

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY/UNDERTAKING

PRODUCT NAME TREADFAST UNITEX PART A
 PRODUCT NO. 10521
 APPLICATION One part of a multi-part smoothing underlayment for floors
 SUPPLIER Tremco illbruck Production Limited
 Coupland Road
 Hindley Green
 Wigan WN2 4HT
 England
 Tel: (+44) 1942 258011
 CONTACT PERSON R P Brisbourne
 EMERGENCY TELEPHONE (+44) 1942 258011

2 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification
PORTLAND CEMENT	266-043-4	65997-15-1	60-100%	Xi;R41,R36/37/38. R43.

The Full Text for all R-Phrases are Displayed in Section 16

COMPOSITION COMMENTS

Soluble chromium VI level is less than 0.0002% provided product is stored as recommended and used before the date on the package.

3 HAZARDS IDENTIFICATION

Risk of serious damage to eyes.

May cause sensitisation by skin contact.

CLASSIFICATION Xi;R41. R43.

HUMAN HEALTH

Contact with wet cement may cause irritation, dermatitis or burns.

4 FIRST-AID MEASURES

INHALATION

Move the exposed person to fresh air at once. Get medical attention if any discomfort continues.

INGESTION

DO NOT INDUCE VOMITING! Rinse mouth thoroughly. Drink plenty of water. Get medical attention.

SKIN CONTACT

Rinse the skin immediately with lots of water. Get medical attention if any discomfort continues.

EYE CONTACT

Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes and get medical attention.

5 FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA

The product is non-combustible.

6 ACCIDENTAL RELEASE MEASURES

TREADFAST UNITEX PART A

SPILL CLEAN UP METHODS

Wear necessary protective equipment. Avoid dust formation. Do not contaminate water sources or sewer. Collect into sealed non-metallic container

7 HANDLING AND STORAGE

USAGE PRECAUTIONS

Avoid handling which leads to dust formation. Avoid spilling, skin and eye contact.

STORAGE PRECAUTIONS

Store in a dry place.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Name	Std	LT - ppm	LT - mg/m3	ST - ppm	ST - mg/m3
PORTLAND CEMENT	WEL		4 mg/m3		10 mg/m3

PROTECTIVE EQUIPMENT



ENGINEERING MEASURES

Provide adequate general and local exhaust ventilation.

RESPIRATORY EQUIPMENT

Dust masks should be worn.

HAND PROTECTION

Use protective gloves made of: Rubber, neoprene or PVC.

EYE PROTECTION

Wear dust resistant safety goggles where there is danger of eye contact.

9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Solid Crystals or crystalline		
COLOUR	Grey		
SOLUBILITY	Insoluble in water		
BULK DENSITY	1100- 1600 kg/m3	pH-VALUE, CONC. SOLUTION	10-12

10 STABILITY AND REACTIVITY

STABILITY

Stable under normal temperature conditions.

MATERIALS TO AVOID

Metals Acids.

11 TOXICOLOGICAL INFORMATION

INHALATION

May cause irritation to the respiratory system.

SKIN CONTACT

Contact with wet cement may cause irritation, dermatitis or burns May cause allergic contact eczema.

EYE CONTACT

Risk of serious damage to eyes.

ROUTE OF ENTRY

Inhalation. Ingestion. Skin and/or eye contact.

TREADFAST UNITEX PART A

12 ECOLOGICAL INFORMATION

ECOTOXICITY

High concentrations in water will cause pH to rise which may cause harm to aquatic life.

13 DISPOSAL CONSIDERATIONS

DISPOSAL METHODS

Dispose of waste and residues in accordance with local authority requirements.

14 TRANSPORT INFORMATION

GENERAL

Not classified as hazardous for transport

No transport warning sign required.

15 REGULATORY INFORMATION

LABELLING



Irritant

CONTAINS

PORTLAND CEMENT

RISK PHRASES

- R41 Risk of serious damage to eyes.
- R43 May cause sensitisation by skin contact.

SAFETY PHRASES

- S24/25 Avoid contact with skin and eyes.
- S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- S37/39 Wear suitable gloves and eye/face protection.
- P17 Contains chromium (VI). May produce an allergic reaction.
Contact with wet cement may cause irritation, dermatitis or burns

16 OTHER INFORMATION

REVISION DATE 10/10/2006

REV. NO./REPL. SDS GENERATED 19/12/2002

RISK PHRASES IN FULL

- R36/37/38 Irritating to eyes, respiratory system and skin.
- R41 Risk of serious damage to eyes.
- R43 May cause sensitisation by skin contact.